

XT-4015

POSIFLEX

Specification	XT-4015
Processor	Intel Ivy Bridge G1620, 2.70 GHz, 2M Cache; Intel Ivy Bridge G2120, 3.10 GHz, 3M Cache; Intel Ivy Bridge Core i3-3220, 3.30 GHz, 3M Cache; Intel Ivy Bridge Core i5-3550S, up to 3.70 GHz, 6M Cache; Intel Ivy Bridge Core i7-3770, up to 3.90 GHz, 8M Cache
System Memory	DDR3L, SO-DIMM x 2, max. 16GB
Storage Device	SATA x 2
RAID Function	Optional, RAID 1 (Disk Mirroring)
Intel vPro Support	N/A
TPM Support	N/A
Power Supply	12V/130W
OS Support	Windows 7/POSReady 7/Windows Embedded 8.1 Industry/Windows 10 IoT/Linux per request
Display & Touch	
LCD	15" TFT LCD
Resolution	1024 x 768
Touch	True-flat PCAP touch with multi-touch support (IP65 on front panel)
I/O & Expansion	
Serial Port	4, DB9 x 3 + RJ45 x 1, 5V/12V support on all 4 COM ports
Parallel Port	1, via optional conversion cable through service window
Standard USB Port	USB 2.0 x 5
PoweredUSB Port	Optional 24V x 1 and 12V x 3 via GEN8E Base
LAN Port	10/100/1000 Mb x 2
Display Port	VGA x 1, 12V support for Posiflex monitors
CR Port	1, control 2 CR via optional Y-cable, supporting 12V cash drawer
PS/2 Port	1, via optional conversion cable through service window
UPS Port	Yes, battery optional
Audio	Internal 2W speaker x 1 + Line-out
Expansion Slot	Mini-PCIe slot x 1
Physical Dimension	
Dimension (W x D x H in mm)	372 x 320 x 252.7
Weight (N. W. in kg)	6.2
Environmental	
Operating Condition	0°C - 40°C, 20%RH - 90%RH (Equipped with HDD); 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)
Storage Condition	-20°C - 70°C, 10%RH - 90%RH
Built-in Options	
WiFi	Mini-PCIe WiFi/BT module
Attachment Options	
POS Monitor	Non-touch TFT LCD: 7"/9.7"/12.1"/14"/15"; PCAP touch TFT LCD: 9.7"/14"/15"; Resistive touch TFT LCD: 15"
Line Display	2 x 20 rear-mount VFD/LCD customer line display; 7" color LCD graphical customer line display
Attachment	MSR; iButton; Rotatable 2D Scanner; RFID; Fingerprint Sensor; Keypad

* Designed and Manufactured in Taiwan by Posiflex Technology, Inc.

* The product information and specifications are subject to change without prior notice.

* Please refer to the website for more attachment options.

Certifications	FC CE       	EN20210514V2
----------------	--	--------------

POSIFLEX

POSIFLEX TECHNOLOGY, INC.

No. 23, Datong St., Tucheng Dist., New Taipei City 23679, Taiwan
Tel : +886-2-2268-5577 E-mail : sales@posiflex.com.tw
Fax : +886-2-2268-5388 www.posiflex.com

Authorized Distributor / Reseller

Flexible! Powerful! Elegant!



XT-4015

High-End POS Terminal



In today's retail and hospitality markets, POS terminal is no longer just a cold and hard business tool. It is a part of the store decoration, a part of the store image. Each curve and detail of the POS terminal should add something to the overall mood of the store, to lift the shopping experience of customers.

The XT-4015 features a 15" true-flat PCAP touch screen, beautifully sculptured slim body, and sexily curved base stand, it looks right at home at any elegantly decorated store. More than just good looks, the XT-4015 can be equipped with the lightning fast Intel Core i7 CPU that provides ample muscle power to handle any task imaginable.

Sleek Look

The XT-4015 comes from new Posiflex design language. Slimmer than ever, it is a sharp departure from the traditionally conservative Posiflex terminal design. Every curve and detail of the XT-4015 is carefully thought out to make itself one of the most visually desirable terminals in the market.

Powerful Performance

The XT Series offers a wide range of performances, with the flagship XT-4015 that stands out above everything else. In its heart beats an Intel Core i7 CPU (optional) that is powerful enough to process anything throws at it without even breaking a sweat.

Multi-Position Folding Base (U.S. Patent 9004436)

The XT-4015 provides the selection of two foldable bases, the curvy slim GEN7E base and the larger but practical GEN8E base. The foldable base can be configured into "Flat Folded Mode" to save the shipping package volume, "Low Profile Mode" to allow greater interaction between the cashier and the customer, and the traditional "Full Extended Mode". All this can be achieved with a simple pull of the hidden lever.



Full Extended Mode



Low Profile Mode



Flat Folded Mode



Power Adaptor

UPS Battery

PoweredUSB Ports

Dual LAN

The XT-4015 is equipped with dual LAN ports that allow a dedicated LAN connection for credit card terminal.

GEN8E Base (U.S. Patent 9004436)

Optional GEN8E base integrates internal power adaptor and PoweredUSB port into the base stand, which keeps counters clutter-free.